





SAFETY DATA SHEET

According to 1907/2006, EC Article 31

SECTION 1: IDENTIFICATION	
Product Identifiers	
Name	FastFix Wet Shield
Company Details	
Company	Evo Building Products
Address	Unit 5, 73 Beauchamp Road
	Banksmeadow
	NSW, 2019
	Australia
Telephone	02 9666 1069
Fax	02 9666 1870
Email	info@evobuild.com.au
Recommended Use	Emergency waterproofing membrane, solvent based
SECTION 2: HAZARDS IDENTIFICATION	
Classification of Substance	Flammable Liquid (Cat 3) Acute Toxicity - Oral (Cat 4) Chronic Aquatic Toxicity (Cat 4) Aspiration Hazard (Cat 1)
Label Elements	
Hazard Statements	H226 Flammable liquid H302 Harmful if swallowed H319 Causes serious eye irritation H362 May cause harm to breast-fed children H304 May be harmful if swallowed and enters airways H350 1B May cause cancer H413 May cause long lasting harmful effects to aquatic life
Precautionary Statements	P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking P233 Keep container tightly closed P264 Wash hands thoroughly after handling P270 Do not eat, drink or smoke when using this product P280/1 Use eye/face protection. Use other PPE as required P331 Do NOT induce vomiting Store in a well ventilated place, keep cool If SWALLOWED/IN EYES: immediately call a POISON CENTRE or doctor/physician
Classification 1999/45/EC	Xn:R65, N: R51/53, R10-64 Xn: Harmful, N: Dangerous for the environment

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS					
Chemical Name	Index #	CAS #	EC #	Conc. (%w/w)	Classification
Chlorinated Parrafin (C14-C17)		85535-85-9	287-477-0	1-10%	N; R50/53;R64:R66
Hydrocarbons C9			918-668-5	10-20%	Xn; R65 Xi; R37 N; R51/53
1,3,4 Trimethylbenzene	601-025-00-5	108-67-8	203.604-4	1-10%	R10 Xi; R37 N; R51/53
Quaternary Ammonium Salt		61789-73-9	263-082-9	0-0.5%	Xn; R22 Xi; R38-41 N; R50; R10
Cumene	601-024-00-X	98-82-8	202-704-5	0-0.5%	R10 Xn; R65 Xi; R37 N; R51/53
Methoxypropyl Acetate	607-251-00-0	70657-70-4	274-724-2	0-0.5%	R10 Repr. Cat. 2; R61 Xi; R37
SECTION 4: FIRST AID MEASURES					
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.				
Eye Contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation symptoms persist.				
Skin Contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation symptoms persist.				
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMOTING.				
SECTION 5: FIRE FIGHTING MEASURES					
Extinguishing Media	Carbon oxides				
Special Hazards	Burning produces irritating, toxic and obnoxious fumes				
PPE and Firefighters	Use self-contained breathing apparatus. Wear protective clothing				
SECTION 6: ACCIDENTAL RELEASE MEASURES					
Personal Precautions, Protective Equipment and Emergency Procedures	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area				
Environmental Precautions	Do not allow product to enter drains. Prevent further spillage if safe				
Methods for materials for containment and clearing up	Absorb with inert, absorbent material. Sweep up. Transfer to suitable labelled containers for disposal. Clean spillage area thoroughly with plenty of water				
SECTION 7: HANDLING AND STORAGE					
Precautions for safe handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition. No smoking.				
Conditions for safe storage	Keep in a cool, dry, well ventilated area Keep containers tightly closed. Store in correctly labelled containers.				
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION					
Control Parameters					
Exposure Limit Values					
1,3,5 Trimethylbenzene	DIR: 2009/39 8hTWA mg/m3: 100 STEL mg/m3: -		8hTWA ppm: 20 STEL PPM: - NOT: -		
Cumene	WEL 8hr limit ppm:25 WEL 15min limit ppm:50		WEL 8hr limit mg/m3:125 WEL 15min limit mg/m3: 250		
Exposure Controls					
Appropriate Engineering Controls	Adequate ventilation of the working areas				

Individual measures	Wear chemical protective clothing		
Eye/face protection	Approved safety goggles		
Skin protection	Chemical resistant gloves (PVC)		
Respiratory protection	Wear suitable respiratory equipment when necessary		
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
Information on basic physical and chemical properties			
State	Liquid		
Colour	Grey		
Odour	145-181		
Boiling Point	35		
SECTION 10: STABILITY AND REACTIVITY			
Chemical Stability	Stable under normal conditions		
Reactivity	No information available		
Possibility of hazardous reactions	Oxidising agents		
Conditions to avoid	Heat, sparks, and open flames		
Incompatible materials	No information available		
SECTION 11: TOXICOLOGICAL INFORMATION			
Acute Toxicity	Harmful if swallowed or inhaled		
Skin corrosion	Can cause skin irritation		
Serious eye damage	Can cause serious eye irritation		
Respiratory of skin sensitisation	Dangerous if inhaled, seek immediate medical advice		
Germ cell mutagenicity	No information available		
Carcinogenicity	No information available		
Reproductive toxicity	May cause harm to breast-fed babies		
STOT – Single exposure	No information available		
STOT – repeat exposure	No information available		
Aspiration hazard	No information available		
SECTION 12: ECOLOGICAL INFORMATION			
Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment		
SECTION 13: DISPOSAL CONSIDERATIONS			
Dispose of in compliance with all local and national regulations. Wear suitable protective equipment.			
SECTION 14: TRANSPORT INFORMATION			
Hazard Pictograms			
UN Number	UN1263		
UN Proper Shipping Name	Paint		
Transport Hazard Classes			
ADR/RID	3	Subsidiary Risk	-
IMDG	3	Subsidiary Risk	-
IATA	3	Subsidiary Risk	-
Packing Group	III		

Environmental Hazards	
Environmental hazards	No
Marine pollutant	No
ADR/RID	
Hazard ID	30
Tunnel Category	D/E
IMDG	
EmS Code	F-E-S-E
IATA	
Packing instruction (cargo)	366
Maximum Quantity	220 L
Packing Instruction (Passenger)	355
Maximum Quantity	60 L
Special Precautions	Always store and ship top side up
SECTION 15: REGULATORY INFORMATION	
Symbols	<p>The product is classified in accordance with 67/548/EEC Xn: Harmful, N: Dangerous for the environment</p> 
Risk Phrases	R10 – Flammable R51/53 – Toxic to aquatic organisms, may cause long-term effects in the aquatic environment R64 – May cause harm to breastfed babies R65 – Harmful: may cause lung damage if swallowed
Safety Phrases	S29 – Do not empty into drains S62 – If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label
SECTION 16: OTHER INFORMATION	
Revision Date	2 April 2019
Revisions	This document differs from the previous version to make it compliant with the new GHS guidelines
<p>The information supplied in the safety data sheet is designed only as guidance for the safe use, storage, and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>	