



Safety Data Sheet

FERROPRE 7606 PTA OF 1LT KIT

Page 1 of 9

SDS No. : 319400

V001.4

Date of issue: 14.10.2021

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: FERROPRE 7606 PTA OF 1LT KIT

Intended use: Epoxy resin

Supplier:

Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Route of Exposure</u>
Skin irritation	Category 2	
Serious eye irritation	Category 2A	
Skin sensitizer	Category 1	
Carcinogenicity	Category 1A	Inhalation
Acute hazards to the aquatic environment	Category 2	
Chronic hazards to the aquatic environment	Category 2	

Hazard pictogram:



Signal word:

Danger

Hazard statement(s):	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H350 May cause cancer. H411 Toxic to aquatic life with long lasting effects.
Precautionary Statement(s):	
Prevention:	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves, eye protection, and face protection. P281 Use personal protective equipment as required.
Response:	P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362 Take off contaminated clothing. P391 Collect spillage.
Storage:	P405 Store locked up.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients**Identity of ingredients:**

Chemical ingredients	CAS-No.	Proportion
Talc	14807-96-6	30- < 60 %
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	30- < 60 %
Dolomite	16389-88-1	< 10 %
Quartz (SiO ₂), <1% respirable	14808-60-7	0.1- < 1 %
2,2'-(methylenebis(p-phenyleneoxymethylene))bisoxirane	2095-03-6	< 1 %

Section 4. First aid measures

Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.
Skin:	Immediately flush skin with plenty of water (using soap, if available). Seek medical advice.
Eyes:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention from a specialist.

Inhalation:	Move to fresh air. Keep warm and in a quiet place. If adverse health effects develop seek medical attention.
First Aid facilities:	Eye wash and safety shower Normal washroom facilities
Medical attention and special treatment:	Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media:	Carbon dioxide, foam, powder Fine water spray
Improper extinguishing media:	Water spray jet
Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide. Oxides of nitrogen.
Special protective equipment for fire-fighters:	Wear protective equipment. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).
Additional fire fighting advice:	In case of fire, keep containers cool with water spray. Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions:	Danger of slipping on spilled product. Wear impervious gloves and chemical splash goggles. Ensure adequate ventilation. Avoid skin and eye contact.
Environmental precautions:	Do not empty into drains / surface water / ground water.
Clean-up methods:	Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling:	Gloves and safety glasses should be worn Ensure that workrooms are adequately ventilated. Avoid skin and eye contact.
Conditions for safe storage:	Keep container tightly sealed. Store in a cool, dry place. Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
TALC, (CONTAINING NO ASBESTOS FIBRES) 14807-96-6			2.5				
NUISANCE DUSTS, INHALABLE DUST 16389-88-1	Inhalable dust.		10				
SILICA, CRYSTALLINE: QUARTZ (RESPIRABLE DUST) 14808-60-7	Respirable dust.		0.05				
QUARTZ (RESPIRABLE DUST) 14808-60-7	Respirable dust.		0.05				

None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Eye protection:

Tightly fitting safety goggles

Skin protection:

Use of protective coveralls and long sleeves is recommended.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.
The use of neoprene gloves is recommended.

Respiratory protection:

If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:	white paste
Odor:	Epoxy
Density:	1.60 - 1.66 g/cm3

Section 10. Stability and reactivity

Stability:	Stable under normal conditions of temperature and pressure.
Conditions to avoid:	Avoid heating. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials:

Acids.
Amines.
Bases.
Oxidizing agents.

Hazardous decomposition products:

Thermal decomposition can lead to release of irritating gases and vapors.

Carbon monoxide.
Carbon dioxide.
Oxides of nitrogen.

Section 11. Toxicological information**Health Effects:****Ingestion:**

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin:

This product is irritating to the skin.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.
May cause sensitization by skin contact.

Eyes:

Causes serious eye irritation.

Inhalation:

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Talc 14807-96-6	LD50 LC50 LD50	> 5,000 mg/kg > 2.1 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rat	OECD Guideline 423 (Acute Oral toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	LD50 LD50	> 2,000 mg/kg > 2,000 mg/kg	oral dermal		rat rat	OECD Guideline 420 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Dolomite 16389-88-1	LD50	> 5,000 mg/kg	oral		rat	not specified
Quartz (SiO ₂), <1% respirable 14808-60-7	LD50 LD50	> 5,050 mg/kg > 2,000 mg/kg	oral dermal		rat not specified	not specified not specified
2,2'-[methylenebis(p- phenyleneoxymethylene)] bisoxirane 2095-03-6	LD50 LD50	> 2,000 mg/kg > 2,000 mg/kg	oral dermal		rat rat	OECD Guideline 420 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Talc 14807-96-6	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	not irritating	4 h	rabbit	not specified

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Talc 14807-96-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Talc 14807-96-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-[methylenebis(p-phenyleneoxymethylene)] bisoxirane 2095-03-6	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Talc 14807-96-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian cell transformation assay	with and without without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Talc 14807-96-6	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	oral: gavage		mouse	not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Talc 14807-96-6	NOAEL=100 mg/kg	oral: feed	101 d7 d/w	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	NOAEL=50 mg/kg	oral: gavage	14 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

Ecotoxicity:

Toxic to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Talc	LC50	100,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	not specified
14807-96-6 reaction product: bisphenol-A- (epichlorhydrin)	LC50	1.75 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
25068-38-6 reaction product: bisphenol-A- (epichlorhydrin)	EC50	1.7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
25068-38-6 reaction product: bisphenol-A- (epichlorhydrin)	EC50	> 11 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
25068-38-6 reaction product: bisphenol-A- (epichlorhydrin)	NOEC	4.2 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
25068-38-6 reaction product: bisphenol-A- (epichlorhydrin)	IC50	> 100 mg/l	Bacteria	3 h	activated sludge, industrial	other guideline:
Dolomite 16389-88-1	LC50	> 56,000 mg/l	Fish	96 h	Gambusia affinis	OECD Guideline 203 (Fish, Acute Toxicity Test)
Dolomite 16389-88-1	EC50	265 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Dolomite 16389-88-1	EC50	137 mg/l	Algae	5 d	Nitzschia sp.	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dolomite 16389-88-1	EC0	> 56,000 mg/l	Bacteria	30 min		not specified
Quartz (SiO ₂), <1% respirable 14808-60-7	LC50	> 1,000 mg/l	Fish	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
Quartz (SiO ₂), <1% respirable 14808-60-7	EC50	> 1,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Quartz (SiO ₂), <1% respirable 14808-60-7	EC50	> 1,000 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Quartz (SiO ₂), <1% respirable 14808-60-7	EC0	> 1,000 mg/l	Bacteria	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2,2'-[methylenebis(p- phenyleneoxymethylene)]bisoxirane 2095-03-6	LC50	> 1 - 10 mg/l	Fish	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-[methylenebis(p- phenyleneoxymethylene)]bisoxirane 2095-03-6	EC50	> 1 - 10 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	-------------------------	---------------	--------

reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane 2095-03-6	not readily biodegradable.	aerobic	< 10 %	OECD 301 A - F

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6	3.242				25 °C	EU Method A.8 (Partition Coefficient)

Section 13. Disposal considerations

- Waste disposal of product:** Dispose of in accordance with local and national regulations.
- Disposal for uncleaned package:** Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information**Road and Rail Transport:**

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Marine transport IMDG:

UN no.: 3082
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
Class or division: 9
Packing group: III
EmS: F-A ,S-F
Seawater pollutant: Marine pollutant

Air transport IATA:

UN no.: 3082
Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)
Class or division: 9
Packing group: III
Packing instructions (passenger) 964
Packing instructions (cargo) 964

Further information for transport:

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

Section 15. Regulatory information

Section 16. Other information

Abbreviations/acronyms:

ADGC - Australian Dangerous Goods Code
GHS: Globally Harmonized System
CAS: Chemical Abstracts Service
LD 50: Lethal Dose 50%
OECD: Organization for Economic Cooperation and Development
LC 50: Lethal Concentration 50%
IMDG: International Maritime Dangerous Goods code
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
AIIC - Australian Inventory of Industrial Chemicals (AIIC)
AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue:

Reviewed SDS. Reissued with new date. involved chapters: 1-16

Date of previous issue:

12.06.2020

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.